

V-i215S-M



Flow	42,5 l/min; 1,5 CFM
Vacuum Level (Partial / Total)	0,2 Pa / 15 microns
Motor Power	0,15 kW (0,2 KM)
Compression Stages	2
Power Supply	230 V
Frequency	50 - 60 Hz
Power Cord Length	200 cm
Motor Speed at 50 Hz	3300 rpm
Noise Level	65 dB
Inlet Connection	1/4" SAE
Oil Capacity	0,11 l
Oil Type	mineral, viscosity: 46 mm ² /s
Dimensions	240 x 88 x 183 mm
Weight	4,0 kg
Protection Class	IP44
Operating Temperature	5 - 40°C
Storage Temperature	-20 - 60°C
Minimum Oil Temperature for Startup	5°C
Shut-Off Valve	yes

V-i215S-M

Exhaust Plug Thread	M24 x 1,5 mm
Vacuum Gauge	no
Packaging	cardboard box

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

V-i215S-M

The vacuum pump VALUE is designed to work with refrigerants like HFC and HCFC (eg R410A, R407C). Dual stage vacuum pump in small size is used in refrigeration and air conditioning.

The main features:

- dual-stage
- compact construction and low weight
- sight glass to control the oil level
- the vacuum solenoid valve and preventing back flow of oil into the system
- ability to be powered by 230V voltage or the torque of a screwdriver (the solenoid valve is powered by 230V)