

## V-i280SV



Flow	198 l/min; 7 CFM
Vacuum Level (Partial / Total)	0,2 Pa / 15 microns
Motor Power	0,74 kW (1 KM)
Compression Stages	2
Power Supply	230 V
Frequency	50 - 60 Hz
Power Cord Length	200 cm
Motor Speed at 50 Hz	1400 rpm
Noise Level	65 dB
Inlet Connection	1/4" SAE
Oil Capacity	0,5 l
Oil Type	mineral, viscosity: 46 mm <sup>2</sup> /s
Dimensions	395 x 145 x 318 mm
Weight	17,0 kg
Protection Class	IP44
Operating Temperature	5 - 40°C
Storage Temperature	-20 - 60°C
Minimum Oil Temperature for Startup	5°C
Shut-Off Valve	yes

## V-i280SV

Exhaust Plug Thread	M33 x 1,5 mm
Vacuum Gauge	external
Vacuum Gauge Size	80 mm
Vacuum Gauge Accuracy	class 1.6
Vacuum Gauge Units	psi / MPa / mbar
Packaging	cardboard box

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

---

## V-i280SV

---

The vacuum pump VALUE is designed to work with refrigerants like HFC and HCFC (eg R410A, R407C). Dual stage vacuum pump is used in refrigeration and air conditioning.

The main features:

- gas ballast valve – prevents moisture from entering the pump oil
- dual-stage
- compact construction
- sight glass to control the oil level
- precision vacuum gauge
- the vacuum solenoid valve and preventing back flow of oil into the system