

## VRP-6DI



Flow	170 l/min; 6 CFM
Vacuum Level (Partial / Total)	0,2 Pa / 15 microns
Motor Power	0,55 kW (0,75 KM)
Compression Stages	2
Power Supply	230 V
Frequency	50 - 60 Hz
Power Cord Length	200 cm
Motor Speed at 50 Hz	2000 rpm
Noise Level	68 dB
Inlet Connection	1/4" i 3/8" SAE
Oil Capacity	0,6 l
Oil Type	mineral, viscosity: 68 mm <sup>2</sup> /s
Dimensions	346 x 145 x 302 mm
Weight	11,5 kg
Protection Class	IP44
Operating Temperature	5 - 40°C
Storage Temperature	-20 - 60°C
Minimum Oil Temperature for Startup	5°C
Shut-Off Valve	yes

## VRP-6DI

Exhaust Plug Thread	M33 x 1,5 mm
Vacuum Gauge	internal electronic
Vacuum Gauge Size	32 x 26 mm
Vacuum Gauge Accuracy	0,1 Pa
Vacuum Gauge Units	Pa / mBar / mmHg / micron
Motor type	DC
Packaging	cardboard box

Pictures of some products may vary. Every effort has been made to ensure that the information contained in this catalog is correct. Due to constant technological development, we reserve the right to make changes without notice.

## VRP-6DI

Smart digital dual-stage vacuum pump VALUE designed for refrigerants from HFC and HFO groups (ex.: R32, 1234yf).

Main features:

- dual-stage
- lightweight, small, high quality vacuum
- large and clear oil inspection eyelet
- digital display
- built-in solenoid valve
- non-sparking design, suitable for R-32 and R-1234yf
- automatic extension of evacuation time depending on the reading
- gas ballast valve – prevents moisture from entering the pump oil



## VRP-6DI

