

SPECIFICATIONS

- BODY: Brass or lead-free brass
- STEM: Brass
- BALL: Chrome plated brass
- SEAT: PTFE
- HANDLE: Plated steel or aluminum
- CONNECTION: 1/4 NPT
- MAXIMUM PRESSURE:
 - Water, Oil, Gas: 600 psi
 - Working Steam: 150 psi
- MAXIMUM TEMPERATURE:
 - Water, Oil, Gas: 225°F/107°C
 - Working Steam: 366°F/185°C
- MARKED: 600WOG-PSI -or- PN 40-BAR

OPTIONS

- Other Connection Sizes
 - 1/2 NPT
 - 3/4 NPT
- Alternate Materials (consult factory)
- Alternate Connections (consult factory)

FEATURES

- Cost-Effective Gauge Isolation Valve
- Quick-Opening
- Lead-Free Brass Available for Potable Water Service



ITEM NUMBERS

Model	Connection	Material
LH-14FF	1/4 NPT FxF	Brass
LH-14MF	1/4 NPT MxF	Brass
LF-14FFLF	1/4 NPT FxF	Lead Free Brass
LF-14MFLF	1/4 NPT MxF	Lead Free Brass
LH-12FF	1/2 NPT FxF	Brass
LH-34FF	3/4 NPT FxF	Brass